



**NEW STOP SIGN  
 NEW PED CROSSWALK**

**NEW STOP SIGN**

**SITE KEYNOTES:**

- ① (N) CROSS WALK STRIPING, SEE DETAIL F/C6.0
  - ② (N) "STOP" PAVEMENT MARKING AND 12" STOP BAR STRIPING. PAINT WITH 2 COATS OF WHITE ACRYLIC LATEX TRAFFIC PAINT, DRY BETWEEN COATS. SEE DETAIL A/C6.0
  - ③ (N) TRUNCATED DOMES, CONCRETE ADA COMPLIANT PAVER. PAVER TO BE PER 2019 CBC SEC. 11B-406.5.12 COMPLIANT PER CALIFORNIA NON-RESIDENTIAL DISABLED ACCESS REGULATIONS OF THE LATEST REVISION. COLOR TO BE RED TO MATCH (E) DOMES IN AREA. PAVERS TO BE SET IN CONCRETE, SEE DETAIL B/C6.0
  - ④ (N) STOP SIGN (MUTCD R1-1 AND R1-3P). SEE DETAIL C/C6.0
  - ⑤ (N) 4" WIDE WHITE STRIPING. PAINT WITH 2 COATS OF WHITE ACRYLIC LATEX TRAFFIC PAINT, DRY BETWEEN COATS
  - ⑥ (N) ROLLED AC DIKE TO FOLLOW (E) EDGE OF PAVEMENT. SEE DETAIL D/C6.0
  - ⑦ (N) 8-FOOT WIDE DG WALKWAY. SEE DETAIL E/C6.0
  - ⑧ (N) 3-FOOT TALL SPLIT RAIL FENCE TO MATCH EXISTING. USE SALVAGE WOOD IF POSSIBLE.
  - ⑨ (N) LANDSCAPING BY OWNER.
  - ⑩ (E) SIGNS TO REMAIN, PROTECT IN PLACE.
  - ⑪ (N) STOP AHEAD SIGN (MUTCD W3-1). SEE DETAIL C/C6.0
  - ⑫ (E) STOP SIGN TO BE REMOVED AND SALVAGED. INSTALL (N) STOP SIGN (MUTCD R1-1 AND R1-3P). SEE DETAIL C/C6.0
  - ⑬ (N) 4" WIDE YELLOW STRIPING. PAINT WITH 2 COATS OF YELLOW ACRYLIC LATEX TRAFFIC PAINT, DRY BETWEEN COATS
  - ⑭ SLURRY COAT (E) ASPHALT ISLAND, PAINT CURBS WITH 2 COATS OF WHITE ACRYLIC LATEX TRAFFIC PAINT, DRY BETWEEN COATS
- CALTRANS CLASS 2 SLURRY COAT WITH BLACK ROCK ( 14,300 SF)

**SITE PLAN**

A  
 C3.0  
 SCALE: 1"=16'